



SECTION I: PRODUCT INFORMATION

PRODUCT: SIKA® VISCOCRETE® 2100 REVISION DATE: January 15th, 2015

USAGE: Water reducing admixture

MANUFACTURER/SUPPLIER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: Not Regulated WHMIS Classification: D2B
UN NUMBER: Not Established Class: Not Applicable
Packaging Group: Not Applicable

SECTION II: HAZARDOUS INGREDIENTS

Table with 6 columns: Hazardous ingredients, %, T.L.V., # CAS, LD50 (mg/kg) (species, route), LC50 (species, route). The table contains one row with 'None on the IDL' and several empty rows.

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Liquid
Appearance and Odor: Light blue liquid, characteristic odor
Odor Threshold: Not Established
Evaporation Rate: < 1 (water)
Vapor Density: < 1 (water)
Vapor Pressure: 17 mm (20°C)
Boiling Point: > 100°C
Freezing Point: < 0°C
Density: 1.08 g/ml
Water Solubility: Yes
pH: Not Established
% volatility: < 60
Water/Oil Distribution: Not Established



PRODUCT: SIKA® VISCOCRETE® 2100

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: If Yes, under what conditions:	No	TDG flammability Class:	Not Regulated
Extinguishing methods:	Foam, dry chemical product, CO ₂ , water hose.	Flammable upper limits (% vol.):	Not Established
Special Methods:	Firefighters must wear their usual protection equipment and respiratory equipment. The water hose could be used to cool down the containers and to dissipate the vapors over the spill.	Flammable lower limits (% vol.):	Not Established
		Flash Point (method used):	Not Established
		Auto-ignition temperature:	Not Established
		Dangerous Combustion Products:	Carbon Oxides.
		Protect from mechanical impact:	No
		Protect from static discharge:	No

SECTION V: REACTIVITY DATA

Chemical stability: If not, under what conditions:	Yes	Dangerous decomposition products:	Carbon Oxides.
Incompatibility with other material: If Yes, which ones:	No specific data	Polymerization Risks:	No



PRODUCT: **SIKA[®] VISCOCRETE[®] 2100**

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritation.

Carcinogenicity: Not Established

Skin: May cause skin irritation.

Toxic effects on reproduction: Not Established

Inhalation: May cause irritation to the lungs.

Teratogenicity: Not Established

Ingestion: May cause irritation to the G.I. System.

Mutagenicity: Not Established

Product with synergistic effects: Not Established

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.



PRODUCT: SIKA® VISCOCRETE® 2100

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Chemical products resistant gloves.

Respiratory equipment: Not necessary.

Eyes: Safety glasses

Shoes: Ordinary

Clothing: Rubber Apron

Other: No

OTHERS

Ventilation: Sufficient ventilation required.

Procedure in case of leaks: Absorb with sand and other absorbent material.

Handling and Equipment methods: Avoid skin, eye and clothing contact.

Warehouse Requirements: Keep all containers closed in a cool, dry area. Protect from freezing.

Special Shipping Instructions: Protect from freezing.

Waste Disposal: Dispose of sand and water according to municipal, provincial and federal laws on chemical waste.

PRODUCT: **SIKA® VISCOCRETE® 2100****SECTION VIII: FIRST AID**

- Skin:** Remove and clean all contaminated clothing.
Wash with plenty of soap and water the exposed areas.
Consult a physician if necessary.
- Eyes:** Clean with water for at least 15 minutes.
Consult a physician if necessary.
- Inhalation:** In the case of overexposure, evacuate to fresh air.
Consult a physician if needed.
- Ingestion:** Do not induce vomiting. Drink plenty of water.
Do not give anything by mouth to an unconscious person.
Consult a physician.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.